



Electrical & Automation

# POWERING A NON-STOP INDIA



**Maximum Retail Prices  
For Final Distribution Products**  
Effective from 01-06-26

# EXORA

# FROM THE COO'S DESK.



Electrical & Automation

Dear Partner,

India is building at a pace and scale that few could have imagined a decade ago. **Infrastructure, metro networks, buildings, green energy corridors, the evolving new energy landscape including solar, modernising factories, and connected homes**, the demand on every link in the electrical and automation value chain has never been greater. It is a privilege to stand at the centre of this transformation, and it is a privilege we share with you.

As we step into this new phase of growth, we are sharing our updated price list. **This revision reflects the investments we continue to make in Made in India manufacturing, R&D, and the service infrastructure that you and your customers rely on every day, across every scale, segment, geography, and across all sources of power.** Our commitment to transparency, quality, and reliability remains the foundation of everything we do together.

At Lauritz Knudsen, we carry over 70+ years of experience built in India, for India. Today, that legacy powers a portfolio spanning **Low Voltage solutions, Industrial Automation, Software and Services**, designed to deliver seamlessly across diverse applications and evolving energy needs. From conventional systems to the rapidly expanding renewable and solar ecosystem, we enable consistent, high performance outcomes that power a **Non Stop India**.

It is your expertise, your relationships, and your reach that turn our solutions into real impact. Every specification advised, every installation completed, every customer served, that is where our shared purpose comes to life. We remain committed to equipping you with the products, training, and support that enable you to deliver with confidence.

As India accelerates toward its Viksit Bharat 2047 vision, the role of reliable, intelligent, and future ready electrical infrastructure has never been more critical. We are ready for what comes next, and we are proud to partner with you on this journey.

Our products and solutions are **built in India and engineered for all**.

**We Listen, We Partner, We Innovate**



A handwritten signature in blue ink, reading "Naresh Kumar".

Warm regards,  
Naresh Kumar  
COO & Sr. VP, Electrical Standard Products  
Lauritz Knudsen Electrical & Automation



# Lauritz Knudsen Electrical & Automation Final Distribution Products

Lauritz Knudsen’s Exora range of modular devices offer MCB, RCCB, Isolator & DB for final distribution of electrical power. Lauritz Knudsen’s products are better known for reliability, functionality & ease of use.



Lauritz Knudsen products conform to relevant global standards viz. IEC, EN. They also have BIS, CE marking, CB and KEMA certification.

## Contents

MCB - Miniature Circuit Breaker	2
Isolators, RCCBs	6
RCBOs - Residual Current Breaker with Overcurrent Protection	8
Other Protection & Control Devices	9
Industrial Plugs & Sockets	11
Distribution Boards	12



### Note:

[Black colour : HSN code]


Current GST 18%, subject to changes as per Govt. notification





### Safety re-defined

Finger proof terminals eliminate chances of accidental contact with live part. You can install, operate and maintain modular device with total confidence.



### Energy limiting class - 3


If fault occurs, the Rapid Arc Quenching mechanism in modular device operates and extinguishes the arc quickly (within 3-5 msec), ensuring lowest possible energy flow through the circuit. This minimize risk of fire and maximizes life of your equipment.



### Safety meets superior aesthetics

Ergonomically designed, profiled for superior cooling and manufactured with fire retardant material. Modular device is brought to you keeping in mind utmost user safety.

## Key Benefits



### True contact indication

E&A modular device range enhances safety through true contact indication even from a distance regardless of its mounting and knob position. Red and Green indication tags provided below the knob positively identify the electrical ON/OFF status, reflecting actual contact status.



### Integrated label holder

E&A MCBs are equipped with label holder for easy identification of circuit during operation as well as in maintenance.




### Innovatively profiled breathing channels

When two or more poles are placed adjacent to each other, the breathing channels are so profiled that the air circulates around individual pole, resulting in cooler operation.




### Large terminal size and Biconnect

Exora MCB's can easily accommodate cables of up to 35 sq.mm. Biconnect terminals offer convenience of connecting both cable and bus bar.




### Two position DIN rail clip

Installation on a DIN rail is further simplified with a two-position DIN rail clip as a standard feature. E&A MCB range makes mounting on a standard DIN rail more convenient .



### Non-welding contacts

Silver Graphite contact tips ensure higher life and maximum safety against contact welding due to its superior anti-welding properties, enhancing safety and life of the system.



### Combihead screw

E&A modular devices with combihead screws, allow you to use standard as well as Philips head screw drivers. E&A modular device range addresses your undefined needs.



# Miniature Circuit Breaker (MCB) [8536]

## Range Highlights

- › True contact indication for individual pole
- › Label holder facility for all configurations
- › Conforms to IS/IEC 60898 - 10kA
- › Conforms to IS/IEC 60947 - 2
  - › 15kA C-curve till 40 A
  - › 10kA C-curve for 50A, 63A
- › Available in B, C & D curves
- › Low watt loss - almost 50% of the values prescribed by IS/IEC 60898
- › Trip free mechanism
- › Design based on advanced current limiting hammer trip mechanism
- › No Line-Load bias
- › Bi connect feature on both sides
- › Suitable for accessory fitment



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>							
0.5A	1	-	-	BB10E50C	610	BB10E50D	635
1A	1	-	-	BB10010C	610	BB10010D	635
2A	1	-	-	BB10020C	610	BB10020D	635
3A	1	-	-	BB10030C	610	BB10030D	635
4A	1	-	-	BB10040C	610	BB10040D	635
6A	1	BB10060B	359	BB10060C	359	BB10060D	530
10A	1	BB10100B	359	BB10100C	359	BB10100D	530
16A	1	BB10160B	359	BB10160C	359	BB10160D	530
20A	1	BB10200B	359	BB10200C	359	BB10200D	530
25A	1	BB10250B	359	BB10250C	359	BB10250D	530
32A	1	BB10320B	359	BB10320C	359	BB10320D	530
40A	1	BB10400B	855	BB10400C	855	BB10400D	930
50A	1	BB10500B	855	BB10500C	855	BB10500D*	930
63A	1	BB10630B	855	BB10630C	855	BB10630D*	930
<b>Double Pole (DP)</b>							
0.5A	2	-	-	BB20E50C	1765	BB20E50D	1795
1A	2	-	-	BB20010C	1765	BB20010D	1795
2A	2	-	-	BB20020C	1765	BB20020D	1795
3A	2	-	-	BB20030C	1765	BB20030D	1795
4A	2	-	-	BB20040C	1765	BB20040D	1795
6A	2	BB20060B	1230	BB20060C	1230	BB20060D	1305
10A	2	BB20100B	1230	BB20100C	1230	BB20100D	1305
16A	2	BB20160B	1230	BB20160C	1230	BB20160D	1305
20A	2	BB20200B	1230	BB20200C	1230	BB20200D	1305
25A	2	BB20250B	1230	BB20250C	1230	BB20250D	1305
32A	2	BB20320B	1230	BB20320C	1230	BB20320D	1305
40A	2	BB20400B	2005	BB20400C	2005	BB20400D	2130
50A	2	BB20500B	2005	BB20500C	2005	BB20500D*	2130
63A	2	BB20630B	2005	BB20630C	2005	BB20630D*	2130
<b>Three Pole (TP)</b>							
0.5A	3	-	-	BB30E50C	2570	BB30E50D	2610
1A	3	-	-	BB30010C	2570	BB30010D	2610
2A	3	-	-	BB30020C	2570	BB30020D	2610
3A	3	-	-	BB30030C	2570	BB30030D	2610
4A	3	-	-	BB30040C	2570	BB30040D	2610
6A	3	BB30060B	1940	BB30060C	1940	BB30060D	2080
10A	3	BB30100B	1940	BB30100C	1940	BB30100D	2080
16A	3	BB30160B	1940	BB30160C	1940	BB30160D	2080
20A	3	BB30200B	1940	BB30200C	1940	BB30200D	2080
25A	3	BB30250B	1940	BB30250C	1940	BB30250D	2080
32A	3	BB30320B	1940	BB30320C	1940	BB30320D	2080
40A	3	BB30400B	3020	BB30400C	3020	BB30400D	3220
50A	3	BB30500B	3020	BB30500C	3020	BB30500D*	3220
63A	3	BB30630B	3020	BB30630C	3020	BB30630D*	3220

**Note:** Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

\*For details, please contact nearest branch office

## Miniature Circuit Breaker (MCB) [8536]



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Four Pole (FP)</b>							
0.5A	4	-	-	BB40E50C	3265	BB40E50D	3270
1A	4	-	-	BB40010C	3265	BB40010D	3270
2A	4	-	-	BB40020C	3265	BB40020D	3270
3A	4	-	-	BB40030C	3265	BB40030D	3270
4A	4	-	-	BB40040C	3265	BB40040D	3270
6A	4	BB40060B	2710	BB40060C	2710	BB40060D	2830
10A	4	BB40100B	2710	BB40100C	2710	BB40100D	2830
16A	4	BB40160B	2710	BB40160C	2710	BB40160D	2830
20A	4	BB40200B	2710	BB40200C	2710	BB40200D	2830
25A	4	BB40250B	2710	BB40250C	2710	BB40250D	2830
32A	4	BB40320B	2710	BB40320C	2710	BB40320D	2830
40A	4	BB40400B	3800	BB40400C	3800	BB40400D	4185
50A	4	BB40500B	3800	BB40500C	3800	BB40500D*	4185
63A	4	BB40630B	3800	BB40630C	3800	BB40630D*	4185

**Note:** Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

\*For details, please contact nearest branch office

## MCBs (Miniature Circuit Breakers) : 80A-125A [8536]

### Range Highlights

- › Short circuit Breaking Capacity - 15kA (IS/IEC 60947-2, EN 60947-2)
- › C & D Characteristics
- › Available in SP, DP, TP and FP
- › Suitable for Isolation
- › Protection Degree - IP 20
- › Availability of wide Range of Site Mountable Accessories



Rating	Modules 1 Mod = 17.5 mm	C Curve Cat. No.	M.R.P. (₹) Per Unit	D Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>					
80A	1.5	AU15S10803C	3685	AU15S10803D	4195
100A	1.5	AU15S11003C	4130	AU15S11003D	4690
125A	1.5	AU15S11253C	4445	AU15S11253D	5070
<b>Double Pole (DP)</b>					
80A	3	AU15S20803C	8160	AU15S20803D	9290
100A	3	AU15S21003C	8705	AU15S21003D	9900
125A	3	AU15S21253C	9580	AU15S21253D	10890
<b>Three Pole (TP)</b>					
80A	4.5	AU15S30803C	12875	AU15S30803D	14660
100A	4.5	AU15S31003C	13735	AU15S31003D	15610
125A	4.5	AU15S31253C	15240	AU15S31253D	17320
<b>Four Pole (FP)</b>					
80A	6	AU15S40803C	16820	AU15S40803D	19100
100A	6	AU15S41003C	17495	AU15S41003D	19905
125A	6	AU15S41253C	19815	AU15S41253D	22520

**CERTIFIED TO LEAD,  
TRUSTED FOR SAFETY.**

BIS-Certified HR MCBs Range - 80A, 100A & 125A



## Solar Combo MCBs [8536]

(AC MCB + DC MCB)



AC MCB<sup>^</sup> with C-Curve

Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
1 AC 16A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC221616	2015
<b>New</b> 1 AC 20A DP MCB <sup>^</sup> + 1 DC 20A DP 500V MCB	2+2	SC222020	2015
<b>New</b> 1 AC 20A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC222025	2015
<b>New</b> 1 AC 20A DP MCB <sup>^</sup> + 1 DC 32A DP 500V MCB	2+2	SC222032	2015
1 AC 25A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC222516	2015
<b>New</b> 1 AC 25A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC222525	2015
1 AC 32A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC223216	2015
<b>New</b> 1 AC 32A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC223225	2015
1 AC 32A DP MCB <sup>^</sup> + 1 DC 32A DP 500V MCB	2+2	SC223232	2015

# Double the Protection, Twice the Power!

## Complete Protection for Solar Rooftop Installations

**DC MCB:**  
10kA as per IEC 60947-2

**AC MCB:**  
10kA as per IS/IEC 60898-1



## Miniature Circuit Breaker (MCB) [8536]

### DC MCBs as per IEC 60947-2 [8536]

Rated Voltage:  
Breaking capacity of 6 kA - BB Series DC MCBs

#### 130V DC SP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>			
0.5A	1	BB10E5DC	860
1A	1	BB1001DC	860
2A	1	BB1002DC	860
3A	1	BB1003DC	860
4A	1	BB1004DC	860
6A	1	BB1006DC	745
10A	1	BB1010DC	745
16A	1	BB1016DC	745
20A	1	BB1020DC	745
25A	1	BB1025DC	745
32A	1	BB1032DC	745
40A	1	BB1040DC	980
50A	1	BB1050DC	980
63A	1	BB1063DC	980



Rated Voltage:  
Breaking capacity of BJ Series DC MCBs  
» 10kA till 40 A  
» 6kA for 50A, 63A

#### 250V DC SP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>			
0.5A	1	BJ10E5DC	1010
1A	1	BJ1001DC	1010
2A	1	BJ1002DC	1010
3A	1	BJ1003DC	1010
4A	1	BJ1004DC	1010
6A	1	BJ1006DC	825
10A	1	BJ1010DC	825
16A	1	BJ1016DC	825
20A	1	BJ1020DC	825
25A	1	BJ1025DC	825
32A	1	BJ1032DC	825
40A	1	BJ1040DC	1140
50A	1	BJ1050DC	1140
63A	1	BJ1063DC	1140

**New**

#### 250V DC DP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
0.5A	2	BB20E5DC	1840
1A	2	BB2001DC	1840
2A	2	BB2002DC	1840
3A	2	BB2003DC	1840
4A	2	BB2004DC	1840
6A	2	BB2006DC	1620
10A	2	BB2010DC	1620
16A	2	BB2016DC	1620
20A	2	BB2020DC	1620
25A	2	BB2025DC	1620
32A	2	BB2032DC	1620
40A	2	BB2040DC	2190
50A	2	BB2050DC	2190
63A	2	BB2063DC	2190



#### 500V DC DP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
0.5A	2	BJ20E5DC	2105
1A	2	BJ2001DC	2105
2A	2	BJ2002DC	2105
3A	2	BJ2003DC	2105
4A	2	BJ2004DC	2105
6A	2	BJ2006DC	1780
10A	2	BJ2010DC	1780
16A	2	BJ2016DC	1780
20A	2	BJ2020DC	1780
25A	2	BJ2025DC	1780
32A	2	BJ2032DC	1780
40A	2	BJ2040DC	2265
50A	2	BJ2050DC	2265
63A	2	BJ2063DC	2265

**New**

Note: Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos.

### 1000V DC MCBs [8536]

Rated Voltage: 1000V DC  
with breaking capacity of 6 kA - BK Series DC MCBs

Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
DP 6A 1000V DC 6kA MCB	4	BK2006DC	2710
DP 10A 1000V DC 6kA MCB	4	BK2010DC	2710
DP 16A 1000V DC 6kA MCB	4	BK2016DC	2710
DP 20A 1000V DC 6kA MCB	4	BK2020DC	2710
DP 25A 1000V DC 6kA MCB	4	BK2025DC	2710
DP 32A 1000V DC 6kA MCB	4	BK2032DC	2710
DP 40A 1000V DC 6kA MCB	4	BK2040DC	3295
DP 50A 1000V DC 6kA MCB	4	BK2050DC	3295
DP 63A 1000V DC 6kA MCB	4	BK2063DC	3295

**New**



## Isolators [8536]



### Range Highlights

- › Conforms to IEC 60947-3
- › Utilization category AC-22A
- › Available in DP, TP and FP versions in 40A, 63A, 80A & 100A ratings

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole (DP)</b>			<b>Three Pole (TP)</b>			<b>Four Pole (FP)</b>			
40A	2	BF204000	830	3	BF304000	1440	4	BF404000	1845
63A	2	BF206300	1055	3	BF306300	1660	4	BF406300	1930
80A	2	BF208000	1345	3	BF308000	1820	4	BF408000	2160
100A	2	BF210000	1410	3	BF310000	1940	4	BF410000	2335

**Note:** Standard Pack Quantity for Isolator : DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

## RCCB (Residual Current Circuit Breaker ) [8536]

### Range Highlights

- › Conforms to IS 12640 (Part 1) / IEC 61008-1
- › RCCBs are available in DP and FP versions from 25 to 100A ratings with 30 mA, 100 mA and 300mA sensitivity



- › Truly current operated - operation even at nominal Voltage
- › Operates on Core Balance Current Transformer (CBCT) principle
- › Advanced neutral mechanism

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole (DP)</b>				
25A	30 mA	2	BG202503	3980
	100 mA	2	BG202510	4380
	300 mA	2	BG202530	4380
32A	30 mA	2	BG203203	4550
	100 mA	2	BG203210	5005
	300 mA	2	BG203230	5005
40A	30 mA	2	BG204003	4550
	100 mA	2	BG204010	5005
	300 mA	2	BG204030	5005
63A	30 mA	2	BG206303	5675
	100 mA	2	BG206310	6035
	300 mA	2	BG206330	6035
100A	30 mA	2	BG210003	10195
	100 mA	2	BG210010	10510
	300 mA	2	BG210030	10510

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Four Pole (FP)</b>				
25A	30 mA	4	BG402503	5450
	100 mA	4	BG402510	5705
	300 mA	4	BG402530	5705
32A	30 mA	4	BG403203	5505
	100 mA	4	BG403210	5805
	300 mA	4	BG403230	5805
40A	30 mA	4	BG404003	5505
	100 mA	4	BG404010	5805
	300 mA	4	BG404030	5805
63A	30 mA	4	BG406303	6225
	100 mA	4	BG406310	6655
	300 mA	4	BG406330	6655
100A	30 mA	4	BG410003	10850
	100 mA	4	BG410010	11250
	300 mA	4	BG410030	11250

## RCCBs (Residual Current Circuit Breakers) : Type-Adi (with Added immunity) [8536]



### Range Highlights

- › Wide Range of Current Ratings - 25A to 100A
- › Precise Sensitivities for variety of applications - from 30mA to 300mA
- › 2P & 4P versions
- › Suitable for Isolation
- › Protection Degree - IP 20
- › Availability of wide Range of Site Mountable Accessories
- › Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P Adi</b>				
25A	30mA	2	AURAD202503	7355
	100mA	2	AURAD202510	7695
	300mA	2	AURAD202530	7695
40A	30mA	2	AURAD204003	7805
	100mA	2	AURAD204010	7930
	300mA	2	AURAD204030	7930
63A	30mA	2	AURAD206303	9130
	100mA	2	AURAD206310	9305
	300mA	2	AURAD206330	9305
100A	30mA	2	AURAD210003	13490

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>4P Adi</b>				
25A	30mA	4	AURAD402503	8895
	100mA	4	AURAD402510	9060
	300mA	4	AURAD402530	9060
40A	30mA	4	AURAD404003	9235
	100mA	4	AURAD404010	9380
	300mA	4	AURAD404030	9380
63A	30mA	4	AURAD406303	10055
	100mA	4	AURAD406310	10265
	300mA	4	AURAD406330	10265
100A	30mA	4	AURAD410003	16020
	300mA	4	AURAD410030	16020

# All-Rounder RCDs (RCCB & RCBO)

Specially designed Adi RCDs ensure Safe and Reliable protection for All Applications in AC networks with Pulsating DC along with Harmonics



**Added Immunity**

# RCBOs (Residual Current Breaker with Overcurrent Protection) [8536]

## Range Highlights\*

- › Conforms to IEC 61009-1, IS 12640-2, EN 61009-1
- › Short circuit Breaking Capacity - 10kA
- › Precise Sensitivities for a variety of applications
  - › from 10mA to 300mA
- › Suitable for Isolation

## Type-AC

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P AC*</b>				
6A	10mA	2	AUF3C200601	6710
	30mA	2	AUF3C200603	6710
	100mA	2	AUF3C200610	6850
	300mA	2	AUF3C200630	6930
10A	10mA	2	AUF3C201001	6710
	30mA	2	AUF3C201003	6710
	100mA	2	AUF3C201010	6850
	300mA	2	AUF3C201030	6930
16A	10mA	2	AUF3C201601	6710
	30mA	2	AUF3C201603	6710
	100mA	2	AUF3C201610	6850
	300mA	2	AUF3C201630	6930
20A	30mA	2	AUF3C202003	6710
	100mA	2	AUF3C202010	6850
	300mA	2	AUF3C202030	6930
25A	30mA	2	AUF3C202503	6710
	100mA	2	AUF3C202510	6850
	300mA	2	AUF3C202530	6930
32A	30mA	2	AUF3C203203	6710
	100mA	2	AUF3C203210	6850
	300mA	2	AUF3C203230	6930
40A	30mA	2	AUF3C204003	6710
	100mA	2	AUF3C204010	6850
	300mA	2	AUF3C204030	6930
63A	30mA	4	AUF3C206303	7970
	100mA	4	AUF3C206310	8455
	300mA	4	AUF3C206330	8520
<b>4P AC</b>				
16A	30mA	7.5	AUF3C401603	7205
	100mA	7.5	AUF3C401610	8020
	300mA	7.5	AUF3C401630	8180
20A	30mA	7.5	AUF3C402003	7205
	100mA	7.5	AUF3C402010	8020
	300mA	7.5	AUF3C402030	8180
25A	30mA	7.5	AUF3C402503	7205
	100mA	7.5	AUF3C402510	8020
	300mA	7.5	AUF3C402530	8180
32A	30mA	7.5	AUF3C403203	7440
	100mA	7.5	AUF3C403210	8025
	300mA	7.5	AUF3C403230	8205
40A	30mA	7.5	AUF3C404003	7555
	100mA	7.5	AUF3C404010	8025
	300mA	7.5	AUF3C404030	8230
63A	30mA	7.5	AUF3C406303	9055
	100mA	7.5	AUF3C406310	9225
	300mA	7.5	AUF3C406330	9225
80A	30mA	12	AUF3C408003	35090
	100mA	12	AUF3C408010	35875
	300mA	12	AUF3C408030	35875
100A	30mA	12	AUF3C410003	37515
	100mA	12	AUF3C410010	38410
	300mA	12	AUF3C410030	38410



- › Availability of wide Range of Site Mountable Accessories
- › Available in
  - › Type AC: For standard AC installations
  - › Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

## Type-Adi

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P Adi</b>				
6A	30mA	2	AUF3D200603	9055
	100mA	2	AUF3D200610	9975
	300mA	2	AUF3D200630	10350
	30mA	2	AUF3D201003	9055
10A	100mA	2	AUF3D201010	9975
	300mA	2	AUF3D201030	10350
	30mA	2	AUF3D201603	9055
16A	100mA	2	AUF3D201610	9975
	300mA	2	AUF3D201630	10350
	30mA	2	AUF3D202003	9055
20A	100mA	2	AUF3D202010	9975
	300mA	2	AUF3D202030	10350
	30mA	2	AUF3D202503	9055
25A	100mA	2	AUF3D202510	9975
	300mA	2	AUF3D202530	10350
	30mA	2	AUF3D203203	9055
32A	100mA	2	AUF3D203210	9975
	300mA	2	AUF3D203230	10350
	30mA	2	AUF3D204003	9055
40A	100mA	2	AUF3D204010	9975
	300mA	2	AUF3D204030	10350
	30mA	4	AUF3D206303	10475
63A	100mA	4	AUF3D206310	11080
	300mA	4	AUF3D206330	11180
	<b>4P Adi</b>			
16A	30mA	7.5	AUF3D401603	9465
	100mA	7.5	AUF3D401610	10525
	300mA	7.5	AUF3D401630	10740
20A	30mA	7.5	AUF3D402003	9465
	100mA	7.5	AUF3D402010	10525
	300mA	7.5	AUF3D402030	10740
25A	30mA	7.5	AUF3D402503	9465
	100mA	7.5	AUF3D402510	10525
	300mA	7.5	AUF3D402530	10740
32A	30mA	7.5	AUF3D403203	9765
	100mA	7.5	AUF3D403210	10535
	300mA	7.5	AUF3D403230	10755
40A	30mA	7.5	AUF3D404003	9915
	100mA	7.5	AUF3D404010	10535
	300mA	7.5	AUF3D404030	10800
63A	30mA	7.5	AUF3D406303	11880
	100mA	7.5	AUF3D406310	12120
	300mA	7.5	AUF3D406330	12120
80A	30mA	12	AUF3D408003	35090
	100mA	12	AUF3D408010	35875
	300mA	12	AUF3D408030	35875
100A	30mA	12	AUF3D410003	37515
	100mA	12	AUF3D410010	38410
	300mA	12	AUF3D410030	38410

\*For technical details, please contact nearest branch office

## SPDs (Surge Protection Devices) [8536]



### Range Highlights

- › Conforms to IEC 61643-11
- › Available in Type 2 and Type 1+2
- › Type 2 : Protection against indirect lightning and switching surges
  - » Maximum Discharge Current - I<sub>max</sub> up to 70kA
- › Type 1+2 : Protection against direct and indirect lightning surges
  - » Maximum Discharge Current - I<sub>max</sub> up to 100kA



### 440V Application (Common + Differential Mode)

Description	I <sub>max</sub>	Configuration	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Type 1+2, I <sub>imp</sub> 12.5kA	50kA	1P+N	2	AUSP121PN50D	13750
		3P+N	4	AUSP123PN50D	26335
Type 2	40kA	1P+N	1	AUSP021PN40D	8595
		3P+N	2	AUSP023PN40D	17175
Type 2	15kA	1P+N	1	AUSP021PN15D	6875
		3P+N	2	AUSP023PN15D	13525
Type 1+2, I <sub>imp</sub> 8kA	100kA	1P+N	2	AUSP121PN100D	12360
		3P+N	4	AUSP123PN100D	24290
Type 2	70kA	1P+N	2	AUSP021PN70D	13500
		3P+N	4	AUSP023PN70D	22485

### 800V Solar Application

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage (Uc)	Cat. No.	M.R.P. (₹) Per Unit
Type 2, I <sub>max</sub> 40kA	3P	4	1500	AUSP023P40-1500	17250
Type 1+2, I <sub>imp</sub> 12.5kA	3P	5	1360	AUSP123P50-1360	51750
Type 1+2, I <sub>imp</sub> 12.5kA	3P	4	880	AUSP123P50-880	35500

### SPD Cartridges

Description	Cat. No.	M.R.P. (₹) Per Unit
Cartridge for AUSP021PN15D	AUSC021PN15D	3380
Cartridge for AUSP021PN40D	AUSC021PN40D	4210
Cartridge for AUSP021PN70D / AUSP023PN70D	AUSC021PN70D	4500
Cartridge for AUSP023PN15D <sup>#</sup>	AUSC023PN15D	4420
Cartridge for AUSP023PN40D <sup>#</sup>	AUSC023PN40D	5620
Cartridge for AUSP121PN100D / AUSP123PN100D	AUSC121PN100D	6745
Cartridge for AUSP121PN50D / AUSP123PN50D	AUSC121PN50D	7280
Cartridge for AUSP023PN15D <sup>#</sup>	AUSC023PN15DG	4900
Cartridge for AUSP023PN40D <sup>#</sup>	AUSC023PN40DG	5115

<sup>#</sup>For technical details, please contact nearest branch office

## ACCL (Automatic Changeover with Current Limiter) [8536]

### Single Phase ACCL



### Range Highlights

- › Conforms to IEC 60947-6, IEC 60947-3
- › Wide Range of Current Ratings
  - » (Generator side) - 1A to 30A
  - » (Electricity Board side) - 30A
- › RoHS compliant

Description EB/DG	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
30A/1A	4	AUCL01030001	3045
30A/1.5A	4	AUCL010301E5	3045
30A/2A	4	AUCL01030002	3045
30A/2.5A	4	AUCL010302E5	3045
30A/3A	4	AUCL01030003	3045
30A/4A	4	AUCL01030004	3045
30A/5A	4	AUCL01030005	3045
30A/6A	4	AUCL01030006	3045
30A/8A	4	AUCL01030008	3045
30A/10A	4	AUCL01030010	3045
30A/12A	4	AUCL01030012	3045
30A/15A	4	AUCL01030015	3045
30A/20A	4	AUCL01030020	3045
30A/30A	4	AUCL01030030*	3045

\*Non-current limiting variant

### Three Phase ACCL



### Range Highlights

- › Settable overload current limit at DG side
- › Separate power consumption monitoring for Mains & Genset
- › Settable overvoltage & undervoltage protection
- › Settable TPN or SPN mode at DG side
- › Protection against single phasing

Description (AC-1) EB/DG	Cat. No.	M.R.P. (₹) Per Unit
32A / 32A	AUCL03032032	18415
40A / 32A	AUCL03040032	18975
40A / 40A	AUCL03040040	20540
50A / 50A	AUCL03050050	29275
63A / 50A	AUCL03063050	32300
63A / 63A	AUCL03063063	36590
80A / 80A	AUCL03080080	55765
125A / 125A	AUCL03125125	93870

For 3 Phase ACCL programming video please scan the QR code or click here



## Changeover Switches [8536]



### Range Highlights

- › Conforms to IEC 60947-3 and IS/IEC 60947-3
- › Available in 3 positions (I-O-II) with centre off position
- › Utilization category AC-22A

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole</b>			
25A	2	AUC00202500	2270
40A	2	AUC00204000	3475
63A	3	AUC00206300	4040
<b>Four Pole</b>			
40A	4	AUC00404000	5985
63A	6	AUC00406300	6785

## Accessories

### Accessories [8538]



All Half Module and One Module Accessories are common for AU MCBs, RCCBs and RCBs

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage	CAT Nos.	M.R.P. (₹) Per Unit
Auxiliary Contact	1NO+1NC	0.5	240V AC, 24V DC	AUAXAC240	1255
AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240	1470
HR AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240HR	1470
Undervoltage Release	-	1	240V AC	AUUVAC240	2965
	-	1	24V DC	AUUVDC024	2965
Overvoltage Release	-	1	240V AC	AUOVAC240	3665
Shunt Release	-	1	240V AC	AUSRAC240	3400
	-	1	24V DC	AUSRDC024	3400
Padlock-Suitable for Lock Hasp 3.5 - 5 mm dia. max	Suitable for 1Pole=1Mod devices: RCCBs, RCBs, Changeover Switches up to 40A			AUPD01	670
	Suitable for 1Pole-1.5Mod devices: MCBs 80A-125A, Changeover Switch 63A			AUPD02	755

**Note:** Standard Pack Quantity for Padlock - 2 Nos.

\*For 80A-125A MCBs please contact nearest branch office

## Control & Monitoring Devices

### Modular Contactors [8536]



### Range Highlights

- › Wide Range of Current Ratings:
  - › 25A, 40A and 63A
- › Conforms to :
  - › IEC 61095, EN 61095
  - › IEC 60947-4-1, EN 60947-4-1
  - › IEC 60947-5-1
- › Protection Degree IP 20

Description (AC-1)	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
25A-1NO	1	AUMC1002501	2545
25A-2NO	1	AUMC2002501	3195
40A-2NO	3	AUMC2004003	5465
40A-3NO	3	AUMC3004003	7830
40A-4NO	3	AUMC4004003	9185
63A-2NO+2NC	3	AUMC2206303	9710
63A-3NO	3	AUMC3006303	9950
63A-4NO	3	AUMC4006303	10955

### Accessory [8538]

Auxiliary Contact, 2NO	0.5	AUMCAUX240	2380
------------------------	-----	------------	------

### Energy Meters [9030]



### Range Highlights

- › DIN mounting whole current operated meter
- › Accuracy Class 1.0
- › Inbuilt RS485 option
- › **Parameters :** Voltage, Current, kW, kWh, kVA, kVAh, RPM, Load hours, Interruptions


Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Single Phase - 60A	2	WD4010100000	3580
Three Phase - 80A	5	WD4020100000	7755
Single Phase - 60A (RS485)	2	WD4010110000	5295
Three Phase - 80A (RS485)	5	WD4020110000	11700

### Indicating Lights [8531]



Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
RED	1	AUIL01RED00	1465
YELLOW	1	AUIL01YEL00	1465
BLUE	1	AUIL01BLU00	1465
GREEN	1	AUIL01GRE00	1465
RED-YELLOW-BLUE	1	AUIL01RYB00	1780

### Auxiliary & Accessories for Exora MCBs [8538]



Description	Cat. No.	M.R.P. (₹) Per Unit
Auxiliary Contact - 6A , 240V AC, (1NO+1NC), 0.5 Mod	BZA11006	1205
Shunt Release - 240V AC, 1 Mod	BZS00240	3295
Trip Alarm Contact - 6A, 240V AC, (1NO+1NC), 0.5 Mod	BZT11006	1405

## Plugs



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Plug - IP44</b>		
16A, 2P+E	PSKPM30164	700
32A, 2P+E	PSKPM30324	1105
16A, 3P+E	PSKPM40164	895
32A, 3P+E	PSKPM40324	1305
16A, 3P+N+E	PSKPM50164	945
32A, 3P+N+E	PSKPM50324	1260
<b>Plug - IP67</b>		
16A, 2P + E	PSKPM30167	1560
32A, 2P + E	PSKPM30327	2200
63A, 2P + E	PSKPM30637	6250
16A, 3P + E	PSKPM40167	1760
32A, 3P + E	PSKPM40327	2785
63A, 3P + E	PSKPM40637	5950
16A, 3P + N + F	PSKPM50167	1885
32A, 3P + N + E	PSKPM50327	2400
63A, 3P + N + E	PSKPM50637	5965
125A, 3P + N + E	PSKPM51257	18215

## Socket



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket - IP44</b>		
16A, 2P+E	PSKSM30164	970
32A, 2P+E	PSKSM30324	1355
16A, 3P+E	PSKSM40164	1140
16A, 3P + N + E	PSKSM50164	1240
32A, 3P + N + E	PSKSM50324	1660
<b>Socket - IP67</b>		
16A, 2P+E	PSKSM30167	1830
32A, 2P+E	PSKSM30327	2515
63A, 2P+E	PSKSM30637	6800
16A, 3P+E	PSKSM40167	2295
63A, 3P+E	PSKSM40637	6865
16A, 3P + N + E	PSKSM50167	2400
32A, 3P + N + E	PSKSM50327	2805
63A, 3P + N + E	PSKSM50637	6975
125A, 3P + N + E	PSKSM51257	21895

## Socket Angled



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket Angled - IP44</b>		
16A, 2P+E	PSKSA30164	755
32A, 2P+E	PSKSA30324	1335
16A, 3P+E	PSKSA40164	1140
32A, 3P+E	PSKSA40324	1575
16A, 3P+N+E	PSKSA50164	1215
32A, 3P+N+E	PSKSA50324	1540
<b>Socket Angled - IP67</b>		
16A, 2P+E	PSKSA30167	1440
32A, 2P+E	PSKSA30327	1875
63A, 2P+E	PSKSA30637	6140
32A, 3P+E	PSKSA40327	2785
63A, 3P+E	PSKSA40637	6150
32A, 3P+N+E	PSKSA50327	2220
63A, 3P+N+E	PSKSA50637	6275
125A, 3P+N+E	PSKSA51257	20820

## Socket Straight



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket Straight- IP44</b>		
16A, 2P+E	PSKSS30164	860
32A, 2P+E	PSKSS30324	1370
32A, 3P+N+E	PSKSS50324	1715
<b>Socket Straight- IP67</b>		
16A, 2P+E	PSKSS30167	1450
63A, 2P+E	PSKSS30637	7435
63A, 3P+E	PSKSS40637	6210
63A, 3P+N+E	PSKSS50637	6210
125A, 3P+N+E	PSKSS51257	20820

# Distribution Board suitable for Aluminum shuttering (Mivan) Construction



## DBs suitable for Aluminum Shuttering Construction [8537]

### SPN DBs

#### Highlights

- › Available in CRCA sheet steel, RAL9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- › With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 43 - Metal Door</b>				
4 way	2	2	LTSD04M	*
6 way	2	4	LTSD06M	*
8 way	2	6	LTSD08M	*
12 way	2	10	LTSD12M	*
16 way	2	14	LTSD16M	*

### TPN DBs

#### Highlights

- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	LTTD04M	*
6 way	8	6+6+6	LTTD06M	*
8 way	8	8+8+8	LTTD08M	*

\* For details, please contact nearest branch office

# DESIGN OR SAFETY?

OBVIOUSLY BOTH. OBVIOUSLY EXORA.N DB.

#ExoraHaiTohSafeHai



**Highlights**

- › Conforms to IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- › With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 30 - Single Door</b>				
4 way	2	2	DESPN004SDS	2060
6 way	2	4	DESPN006SDS	2155
8 way	2	6	DESPN008SDS	2485
12 way	2	10	DESPN012SDS	2950
16 way	2	14	DESPN016SDS	3610
18 way	2	16	DESPN018SDS	4200
<b>IP 43 - Metal Door</b>				
4 way	2	2	DESPN004DDS	2680
6 way	2	4	DESPN006DDS	3090
8 way	2	6	DESPN008DDS	3305
12 way	2	10	DESPN012DDS	3965
16 way	2	14	DESPN016DDS	5015
18 way	2	16	DESPN018DDS	5250
<b>IP 43 - Glazed Door</b>				
4 way	2	2	DESPN004GDS	3590
6 way	2	4	DESPN006GDS	3820
8 way	2	6	DESPN008GDS	4150
12 way	2	10	DESPN012GDS	5055
16 way	2	14	DESPN016GDS	6280
18 way	2	16	DESPN018GDS	6645
<b>IP 54 - Metal Door</b>				
4 way	2	2	DESPN00454S	9355
6 way	2	4	DESPN00654S	10430
8 way	2	6	DESPN00854S	11090
12 way	2	10	DESPN01254S	12735
16 way	2	14	DESPN01654S	14180
18 way	2	16	DESPN01854S	14495

**Highlights**

- › Conforms to IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SPMCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 30 - Single Door</b>				
4 way	4	4+4+4	DETPN004SDS	5360
6 way	4	6+6+6	DETPN006SDS	6580
4 way	8	4+4+4	DETPN004SDS	5645
6 way	8	6+6+6	DETPN006SDS	6990
8 way	8	8+8+8	DETPN008SDS	8245
12 way	8	12+12+12	DETPN012SDS	11880
16 way	8	16+16+16	DETPN016SDS	14485
<b>IP 43 - Metal Door</b>				
4 way	4	4+4+4	DETPN004DDS	6300
6 way	4	6+6+6	DETPN006DDS	7830
4 way	8	4+4+4	DETPN004DDS	6590
6 way	8	6+6+6	DETPN006DDS	8210
8 way	8	8+8+8	DETPN008DDS	9855
12 way	8	12+12+12	DETPN012DDS	14695
16 way	8	16+16+16	DETPN016DDS	18240
<b>IP 43 - Glazed Door</b>				
4 way	4	4+4+4	DETPN004GDS	8555
6 way	4	6+6+6	DETPN006GDS	10285
4 way	8	4+4+4	DETPN004GDS	8905
6 way	8	6+6+6	DETPN006GDS	10840
8 way	8	8+8+8	DETPN008GDS	12850
12 way	8	12+12+12	DETPN012GDS	19715
16 way	8	16+16+16	DETPN016GDS	23695
<b>IP 54 - Metal Door</b>				
4 way	4	4+4+4	DETPN00454S	21375
6 way	4	6+6+6	DETPN00654S	24980
4 way	8	4+4+4	DETPN00454S	22590
6 way	8	6+6+6	DETPN00654S	27205
8 way	8	8+8+8	DETPN00854S	29740
12 way	8	12+12+12	DETPN01254S	41920
16 way	8	16+16+16	DETPN01654S	50305

For ordering old DBs, replace Cat no with "DB" instead of "DE".  
 Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

**Highlights**

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB / Isolator / RCCB / RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



**Horizontal PPI DBs**

IP 43 - Metal Door

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	8	2+2+2	4+4+4	DEHPI004DD	11720
6 way	8	2+2+2	6+6+6	DEHPI006DD	13875
8 way	8	2+2+2	8+8+8	DEHPI008DD	16640
12 way	8	2+2+2	12+12+12	DEHPI012DD	22930
16 way	8	2+2+2	16+16+16	DEHPI016DD	27510



**Tier PPI DBs**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
6 way	8	2+2+2	6+6+6	DETPPI006DD	14360
8 way	8	2+2+2	8+8+8	DETPPI008DD	18005
10 way	8	2+2+2	10+10+10	DETPPI010DD	18870
12 way	8	2+2+2	12+12+12	DETPPI012DD	19995
16 way	8	2+2+2	16+16+16	DETPPI016DD	22795
12 way	MCCB*	2+2+2	12+12+12	DETPPL012DD	21385

\*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DN0-100D & DN0-100C MCCB as incomer

**Highlights**

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for
  - » Modular Incomer - FP MCB/Isolator/RCCB/RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing
  - » MCCB Incomer - MCCB\* as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



**With Modular Incomer**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	8	4+4+4	4+4+4	DEPSG004DD	17210
6 way	8	4+4+4	6+6+6	DEPSG006DD	19405
8 way	8	4+4+4	8+8+8	DEPSG008DD	21650
12 way	8	4+4+4	12+12+12	DEPSG012DD	26860



**With MCCB Incomer**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	MCCB	4+4+4	4+4+4	DEPGL004DD	23675
6 way	MCCB	4+4+4	6+6+6	DEPGL006DD	27070
8 way	MCCB	4+4+4	8+8+8	DEPGL008DD	31310
12 way	MCCB	4+4+4	12+12+12	DEPGL012DD	35310

\*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DN0-100D & DN0-100C MCCB as incomer

## Vertical TPN DB with MCCB Incomer [8537]



### Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for 3 pole and 4 Pole MCCB\* as incomer and SP/TP MCCBs as outgoing



### Up to 125A MCCB Incomer

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTL004DD	19205
6 way	MCCB	6+6+6	DEVTL006DD	21825
8 way	MCCB	8+8+8	DEVTL008DD	24030
12 way	MCCB	12+12+12	DEVTL012DD	32690
16 way	MCCB	16+16+16	DEVTL016DD	38995
<b>IP 54 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTL00454	39780
6 way	MCCB	6+6+6	DEVTL00654	45360
8 way	MCCB	8+8+8	DEVTL00854	49105

\*Suitable for 3 Pole & 4 Pole DZO MCCB as incomer.  
In case of any other MCCB frame requirement please contact nearest branch.

## Vertical TPN DB with Modular Incomer [8537]



### Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP/ TP MCCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	DEVTM004DD	16240
6 way	8	6+6+6	DEVTM006DD	18090
8 way	8	8+8+8	DEVTM008DD	21000
12 way	8	12+12+12	DEVTM012DD	28325
16 way	8	16+16+16	DEVTM016DD	33795
<b>IP 54 - Metal Door</b>				
4 way	8	4+4+4	DEVTM00454	34330
6 way	8	6+6+6	DEVTM00654	37450
8 way	8	8+8+8	DEVTM00854	41355

## Vertical TPN DB with MCCB Incomer [8537]



### Up to 250A MCCB Incomer

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTH004DD	24955
6 way	MCCB	6+6+6	DEVTH006DD	27945
8 way	MCCB	8+8+8	DEVTH008DD	30735
12 way	MCCB	12+12+12	DEVTH012DD	37195
16 way	MCCB	16+16+16	DEVTH016DD	49985
<b>IP 54 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTH00454	45655
6 way	MCCB	6+6+6	DEVTH00654	49845
8 way	MCCB	8+8+8	DEVTH00854	51555

\*Suitable for 3 pole and 4 pole DU250, DU250C & DN1 MCCB as incomer

## Flexi/Row DB [8537]



### Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | cable ties | circuit identification labels
- › With provision to mount modular devices as per requirement



Description	No. of Modules Per Row	Cat. Nos.	M.R.P. (₹) Per Unit
<b>IP 43 - Metal Door</b>			
2 Row 28 Module	14	DEROW228DD	8390
3 Row 42 Module	14	DEROW342DD	10055
4 Row 56 Module	14	DEROW456DD	10935
4 Row 64 Module	16	DEROW464DD	12720

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

## TPN Phase Selector DB [8537] New

### Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 3 nos. of 63A E&A rotary switches | 3 nos. of rocker switches for phase identification | 100A insulated phase bus-bars | neutral bar/s with shroud/s | set | earth bar/s | sticking saddles | color-coded interconnecting wire cable ties | blanking plates and circuit identification labels
- › With provision for - FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	DEPSR004DD	21135
6 way	8	6+6+6	DEPSR006DD	21475
8 way	8	8+8+8	DEPSR008DD	23005
10 way	8	10+10+10	DEPSR010DD	24580
12 way	8	12+12+12	DEPSR012DD	25915

## EV charging DB 8537] New

### Highlights

- › Engineered specifically Charging application - 3.3 kW
- › Robust earth leakage, short circuit and overload protection with RCBO-
- › Factory fitted RCBO, switch and socket



Description	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
2 way EVDB	2	DEEVC002LD	*
4 way EVDB	4	DEEVC004LD	*

\* For details, please contact nearest branch office

## Enclosure [8537] New

### Highlights

- › Conforms to IEC 61439-1 & 3
- › Suitable for Surface and Flush mounting
- › Available in CRCA sheet steel, RAL9003, powder coated
- › With provision to mount MCB/Isolator/RCCB/RCBO and other modular devices



## IP 30 - Metal Door

Description	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
<b>IP 30 - Metal Door</b>			
2 way	2	DEENC002SD	1045
3 way	3	DEENC003SD	1045
4 way	4	DEENC004SD	1045
6 way	6	DEENC006SD	1620

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eq. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

## Plug & Socket DB [8537] New

### Highlights

- › Conforms to IEC 61439-1 & 3
- › Suitable for Surface and Flush mounting
- › Available in CRCA sheet steel, RAL9003, powder coated
- › Loose Metal Plugs & Sockets conforms to IS 8804; available in Single Phase & Three Phase



Metal Plug & Socket

Plastic Plug & Socket

Description	No. of Pins	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
<b>Metal Plug &amp; Sockets</b>				
10 A, 2 Pin + SC <sup>^</sup>	P + N	1	DEMPS110SD	2595
20 A, 2 Pin + SC <sup>^</sup>	P + N	1	DEMPS120SD	2790
20 A, 2 Pin + SC <sup>^</sup>	P + N	2	DEMPS220SD	3025
20 A, 3 Pin + SC <sup>^</sup>	3P	3	DEMPS320SD	5125
32 A, 3 Pin + SC <sup>^</sup>	3P	3	DEMPS332SD	6065
32 A, 3 Pin + SC <sup>^</sup>	3P	4	DEMPS432SD	6450
63 A, 5 Pin + SC <sup>^</sup>	3P+N+E	4	DEMPS463SD	21860
<b>Plastic Plug &amp; Sockets</b>				
16 A, 3 Pin	P+N+E	2	DEPPS316SD	4245
32 A, 3 Pin	P+N+E	4	DEPPS332SD	4575
32 A, 5 Pin	3P+N+E	8	DEPPS532SD	7645
63 A, 5 Pin	3P+N+E	8	DEPPS563SD	19160

## Metal Plug [8536]



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC <sup>^</sup>	P + N	MPS210P	320
20 A, 2 Pin + SC <sup>^</sup>	P + N	MPS220P	340
20 A, 3 Pin + SC <sup>^</sup>	3P	MPS320P	450
32 A, 3 Pin + SC <sup>^</sup>	3P	MPS332P	855

Note: Standard pack quantity - 20 nos.

## Metal Socket [8536]



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC <sup>^</sup>	P + N	MPS210S	335
20 A, 2 Pin + SC <sup>^</sup>	P + N	MPS220S	370
20 A, 3 Pin + SC <sup>^</sup>	3P	MPS320S	505
32 A, 3 Pin + SC <sup>^</sup>	3P	MPS332S	855

<sup>^</sup> SC-Scraping Earth

Note: Standard pack quantity - 20 nos.



## Highlights

- › Distribution Boards equipped with provisions to mount TV / Telephone splitters
- › Available in SPN & TPN DBs
- › Communication DB equipped with provisions to mount 2 ONT, Spike guard, Data switch, TV / Telephone splitters



TV / Telephone



Communication DB

## Cable End Boxes [8537]

### Highlights

- › Available in CRCA sheet steel, RAL9003, powder coated
- › Can be either at the top or bottom of the distribution board

Description	Cat. Nos.	M.R.P. (₹) Per Unit
<b>CEB for SPN DBs</b>		
CEB-SPN Double Door, 4 way	DESPN004CBS	1145
CEB-SPN Double Door, 6 way	DESPN006CBS	1235
CEB-SPN Double Door, 8 way	DESPN008CBS	1380
CEB-SPN Double Door, 12 way	DESPN012CBS	1535
CEB-SPN Double Door, 16 way	DESPN016CBS	2160
CEB-SPN Double Door, 18 way	DESPN018CBS	2230
<b>CEB for TPN DBs</b>		
CEB-TPE Double Door, 4 way	DETPN004CBS	1480
CEB-TPE Double Door, 6 way	DETPN006CBS	2110
CEB-TPN Double Door, 4 way	DETPN004CBS	1550
CEB-TPN Double Door, 6 way	DETPN006CBS	2175
CEB-TPN Double Door, 8 way	DETPN008CBS	2735
CEB-TPN Double Door, 12 way	DETPN012CBS	4550
CEB-TPN Double Door, 16 way	DETPN016CBS	4595
<b>CEB for Horizontal PPI DBs</b>		
CEB-Horz. PPI Double Door, 4 way	DEHPI004CB	2295
CEB-Horz. PPI Double Door, 6 way	DEHPI006CB	2865
CEB-Horz. PPI Double Door, 8 way	DEHPI008CB	3595
CEB-Horz. PPI Double Door, 12 way	DEHPI012CB	4510
CEB-Horz. PPI Double Door, 16 way	DEHPI016CB	4905
<b>CEB for VTPN DBs</b>		
CEB-VTPN Double Door, Modular Incomer	DEVTMXXXCB	1535
CEB-VTPN Double Door, MCCB Incomer	DEVTXXXCB	5420
<b>CEB for Phase Segregated DBs</b>		
CEB-PSG Double Door, 4 way	DEPSG004CB	4025
CEB-PSG Double Door, 6 way	DEPSG006CB	4795
CEB-PSG Double Door, 8 way	DEPSG008CB	5295
CEB-PSG Double Door, 12 way	DEPSG012CB	5895

DB Type	Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
		Incomer + Outgoing			
<b>IP 43 - Metal Door</b>					
SPN	6 way	2	4	DESPN006DDTV	5835
	8 way	2	6	DESPN008DDTV	6275
	12 way	2	10	DESPN012DDTV	7720
	16 way	2	14	DESPN016DDTV	8960
	18 way	2	16	DESPN018DDTV	10595
TPN	4 way	8	4+4+4	DETPN004DDTV	11470
	6 way	8	6+6+6	DETPN006DDTV	13255
	8 way	8	8+8+8	DETPN008DDTV	15800
Communication DB				DECOM01DD	*

\* For details, please contact nearest branch office

## DB Accessories

### Busbar - Fork Type [8538]

#### Highlights

- › Available in Single Pole, Double Pole, Three Pole and Four Pole versions
- › Material : Copper



Description	Cat. Nos..	M.R.P. (₹) Per Unit	Std. Pack Qty.
SP 13 Mod	BSP13	510	5
SP 56 Mod	BSP56	2095	5
DP 12 Mod	BDP12	910	5
TP 12 Mod	BTP12	985	5
FP 12 Mod	BFP12	1945	5
End Caps for SP	ECP01	35	10
End Caps for DP/TP	ECP03	70	10
End Caps for FP	ECP04	115	10



### Blanking Plates [8538]

#### Highlights

- › Available in One module and Half module

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std. Pack Qty.
One Module	BKP10	35	10
Half Module	BKP05	35	10



PKD02

### Padlock [8301]

#### Highlights

- › Version with standard lock and a common key

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std. Pack Qty.
Lock and Key Kit	PKD02	890	5

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

## General Terms

All prices are on Maximum retail price basis inclusive of all duties, GST & any other tax as applicable.

## Warranty Policy

All products listed in the price list are covered by a warranty against manufacturing defects for a period of 18\* months from the date of purchase. For Lauritz Knudsen MCBs & Isolators mounted inside Lauritz Knudsen Distribution Boards, an extended warranty of 5 years is provided.

In the event of a defect due to faulty workmanship or other associated reasons, we will, at our discretion, remedy the defect or replace the faulty parts or the entire product as soon as possible, free of cost.

However, the warranty is subject to proper usage, efficient maintenance, and does not cover defects arising from fire, accidents, inefficient maintenance, faulty operation, or deliberate or accidental damage. It also does not cover damage to power electronic components such as thyristors & IGBTs, which primarily fail due to overtemperature & over-voltage. Users need to take adequate precautions to eliminate these conditions. Manufacturer shall not be responsible & liable for any special, incidental, social or consequential (including lost profits) loss, consequential damages, injury or damages (punitive) of any kind solely attributable to defect or failure of its products. Manufacturer shall not be liable in any manner for the issue of or failure in the performance of other equipment the product is attached to.

## Comprehensive Service Support

Lauritz Knudsen Electrical & Automation has over seven decades of experience in providing after sales service for low voltage distribution system in every type of industry & commercial complex in India

Lauritz Knudsen Electrical & Automation offers the following services, partnering you in your maintenance of low voltage distribution products:

- > Regular Maintenance
- > Preventive Maintenance Programme
- > On Call
- > Annual Maintenance Contract
- > Product Support for Managing Obsolescence-

# Switchgear Training Centres



## Pune

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
T-156 / 157, MIDC,  
Bhosari, Pune - 411 026  
Tel: 020-2712 0037 / 2712 0653  
E-mail: STC-PUNE@LK-EA.com



## Lucknow

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
C-6 & 7, UPSIDC,  
P. O. Sarojininagar,  
Lucknow - 226 008  
Tel: 97944 54455  
E-mail: STC-LUCKNOW@LK-EA.com



## Delhi

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
A-25, Imperia Complex, First Floor  
Mohan Cooperative Industrial Estate  
Near Sarita Vihar / Mohan Estate Metro Station  
Main Mathura Road, New Delhi - 110044  
Tel: 9899020306 / 9720186726 / 9560845094  
E-mail: STC-DELHI@LK-EA.com



## Kolkata

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre,  
2nd Floor, Block BN3, Sector V,  
Salt Lake City,  
Kolkata - 700091, West Bengal  
Tel: 7738717893 / 7797795567  
E-mail: STC-KOLKATA@LK-EA.com



## Vadodara

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
Behind L&T Knowledge City,  
Near Village Ankhola,  
Vadodara - 390019  
Tel: 0265 6147805 / 6147808  
E-mail: STC-VADODARA@LK-EA.com



## Coonor

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
Ooty-Coonor Main Road  
Yellanahalli P.O.,  
The Nilgiris - 643 243  
Tel: 0423 251 7107  
E-mail: STC-COONOOR@LK-EA.com

Customer Interaction Center (CIC)  
Phone no: 022 6932 7800  
Web: [www.LK-EA.com](http://www.LK-EA.com) | e-mail: [CIC@LK-EA.com](mailto:CIC@LK-EA.com)



# Electrical Standard Products (ESP) Offices

## HEAD OFFICE

Lauritz Knudsen Electrical & Automation, A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra.

Tel: 022-6722 6300 | Fax: 022-6705 1112 | e-mail: CIC@LK-EA.com

## BRANCH OFFICES

Lauritz Knudsen Electrical & Automation  
C-201, The First Commercial Complex,  
B/S Keshavbaug Party Plot, Vastrapur,  
**Ahmedabad - 380 015**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Shri Daneshwari, 1st Floor,  
Plot No. 17, 2nd Cross, Near Old Income  
Tax Office Road, Vidyanagar,  
**Hubballi - 580 021**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
No.10, Fortuna Towers, 2nd Floor,  
Rana Pratap Marg, Near NBRI,  
**Lucknow - 226 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
A06/A07, Second Floor,  
Grand Chandra Complex, Frazer Road  
**Patna - 800 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Wework Central, #36 Infantry Road,  
**Bengaluru - 560 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
AWFIS Space Solutions, Prestige Phoenix,  
4th floor, 1405, Umanagar, Begumpet,  
**Hyderabad - 500 016**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
El Dorado Building, 3rd Floor, 6,  
Venkatraman Street, Chinna Chokkikulam,  
**Madurai - 625 002**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
UrbanWrk, 5th Floor, Sai Radhe,  
Raja Bahadur Mill Road, Behind Hotel  
Grand Sheraton, Sangamwadi  
**Pune - 411 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Work loop Unit-612, 6th Floor,  
Esplanade One, Rasulgarh,  
**Bhubaneswar - 751 010**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Workie, 214 - 2nd Floor,  
Apollo Premier, PU-4,  
Scheme No. 54, Vijay Nagar Square,  
**Indore - 452 010**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Bestech Business Park,  
Tower - A, 2nd floor, Sector - 66  
**Mohali - 160059**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Office No. 211 & 212, Pithalia Plaza,  
KK Road, Near Fafadih Chowk,  
**Raipur - 492 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
801 Word Level-8, No. 28,  
SIDCO Industrial Estate, Guindy,  
**Chennai - 600 032**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Office No. 430, 4th Floor,  
Jaipur Electronic Market, Riddhi Siddhi,  
Gopalpura Bypass,  
**Jaipur - 302 018**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
TC II, Tower B, PRIMA BAY Gate No. 5,  
Saki Vihar Road Powai,  
**Mumbai - 400 072**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
DevX 4th Floor, A Wing, Om 9 Square,  
150 Ft Ring Road, Near Nana Mava Circle,  
Opp Silver Heights,  
**Rajkot - 360 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Playworkz Coworking Space  
43 & 44, 3rd Cross,  
Bharathy Colony, Peelamedu,  
**Coimbatore - 641 004**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
GDR Siddha, Ground Floor, N Road  
Bistupur, Opposite St. Mary's Church,  
**Jamshedpur - 831 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Unnati Building, 2nd Floor,  
Automation Campus, A-600, TTC Industrial  
Area Shil-Mahape Road, Mahape,  
**Navi Mumbai - 400 710**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
10th Floor, Titanium Business,  
Bhimrad Road, Althan  
**Surat - 395 017**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
3rd Floor, 1&2 Vijay Park,  
Main Chakrata Road, Opp. Anandam,  
Near Ballapur chowk,  
**Dehradun - 248 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Business Communication Centre  
2nd Floor, Chiramel Chambers,  
Kurusipally Road, Ravipuram,  
**Kochi - 682 015**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
M1 & M2, Mezzanine Floor,  
Himalaya Excellency,  
Plot No. C-47, Pratap Nagar Square,  
**Nagpur - 440 022**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
11th Floor, Block-D, Notus IT Park,  
Sarabhai Campus, Bhailal Amin Marg,  
**Vadodara - 390 023**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Ground Floor, B-27,  
Biplab Rashbihari Sarani,  
Sector 2A, Bidhan Nagar,  
**Durgapur - 713 212**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
207, 2nd floor, Revolution Complex,  
Station Road, E Ward,  
Next to Pedestrian Bridge,  
**Kolhapur - 416 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
2nd Floor, Samarth House,  
Opposite Titan World,  
Samarth Nagar, Mahatma Nagar,  
**Nasik - 422 005**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Qubexpro Business Centre,  
4th Floor, V Mall, Above Lifestyles,  
Factor Layout, Waltair Uplands,  
**Visakhapatnam - 530 003**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
6th Floor, Exotica Greens, A Block, 191,  
R G Baruah Road, Guwahati Central,  
**Guwahati - 781 005**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
2nd Floor, BN3, Salt Lake, Sector-V,  
**Kolkata - 700 091**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
A-25, 1st Floor, Imperia Complex,  
Mohan Corporative Industrial Estate,  
Near Sarita Vihar Metro Station,  
Mathura Road,  
**New Delhi - 110 044**  
Phone no: 022-6932 7800  
e-mail: CIC@LK-EA.com

Product improvement is a continuous process. For the latest information and special application, please contact any of our offices listed here. Product photographs shown for representative purpose only.



### Lauritz Knudsen Electrical & Automation, Electrical Standard Product

A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra, Phone No: 022-6722 6300 | Web: www.LK-EA.com

Customer Interaction Center (CIC)

Phone no: 022-6932 7800

Web: www.LK-EA.com | e-mail: CIC@LK-EA.com